

W319ST

Bright and compact short throw projector



- **Bright WXGA projector – 4000 ANSI lumens**
- **Short throw lens - 100" image from just over a metre away**
- **Ultimate control - Crestron, Extron, AMX, PJ-link and telnet LAN commands**
- **Easy connectivity – HDMI, VGA, USB power and 10W speaker**

Project bright vibrant presentations effortlessly any time of day. Designed for small meeting rooms and classrooms, this short throw projector boasts Amazing colour, long lamp life and energy-saving features to provide you with a low overall cost of ownership.

Multiple inputs, USB power and a built-in speaker provide an easy set-up - perfect for connecting to laptop, PC or Blu-ray player for clear projected images with sound. You can even connect a HDMI dongle for wireless presentations.

For ultimate control, the projector comes with RJ45, allowing you to monitor and control your network in multiple rooms.

Specifications

EAN: 5055387665002, Colour: White

Display/image	
Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness	4,000 lumens
Contrast ratio	25,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3, 16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	75%
Screen size	0.91m ~ 7.7m (35.64" ~ 302.98") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	203
Lamp life hours (up to)	6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optical	
Throw ratio	0.52:1
Projection distance (m)	0.4m - 3.4m
Focal length (mm)	7.51mm/0.296"
Native offset	112%
Connectivity	
Connections	Inputs 2 x HDMI 1.4a 3D support, 2 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm, 1 x Mic 3.5mm Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm Control 1 x USB-A power 1A, 1 x RS232, 1 x RJ45
General	
Noise level (typical)	26dB
Noise level (max)	28dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	10W
In the box	AC power cord Remote control 2x AA batteries Basic user manual
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200
Networking	
LAN - control	Yes
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	187W
Power consumption (max)	225W
Weight and dimensions	
Dimensions (W x D x H) mm	316 x 244 x 108
Gross weight	3.93 kg
Net weight	3.34 kg

