

100 ICW5-T

Product Data Sheet



Key Points

- Product designed and developed in France by Focal
- Compact product with shallow mounting depth
- 100V/70V mode by switch
- Ready-to-paint grille

Technical Specifications

Type	In-wall/In-ceiling - 2-way coaxial for 100V/70V line installation
Drivers	5" (13cm) Polyglass Midbass 1" (25mm) Aluminium inverted dome Tweeter
Sensitivity (2.83V/1m)	88dB
Frequency response (+/-3dB)	65Hz - 23kHz
Low frequency point (-6dB)	56Hz
Power in 70V	2/4/7.5W
Power in 100V	4/8/15W
Recommended amplifier power	15 - 100W
External dimensions (Ø/Depth)	7 ¹ / ₄ "x4" (184x100mm)
Cut-Out diameter	6 ³ / ₁₆ " (157mm)
Depth from wall	3 ³ / ₄ " (96mm)
Net weight (with front grille)	3.52lbs (1.6kg)
Packing dimensions (WxDxH)	9 ⁵ / ₈ "x9 ⁵ / ₈ "x6 ¹⁵ / ₁₆ " (245x245x161mm)
Total weight (with packaging)	5.29lbs (2.4kg)

Selectable power table

70V	2W	4W	7.5W
100V	4W	8W	15W

