

L05 Series Optical Bonding AIO Touch Panel_8.0

Donview

Lead Your Presentation To The Next Generation

| Model | | DS-65IWMS-L05PA | DS-75IWMS-L05PA | DS-86IWMS-L05PA |
|--------------------------------|--------------------------------|---|--|---|
| Appearance | Size | 65 inch | 75 inch | 86 inch |
| | Type | a-Si TFT-LCD | a-Si TFT-LCD | a-Si TFT-LCD |
| | Aspect Ratio | 16:9 | 16:9 | 16:9 |
| | Backlight | LED | LED | LED |
| | Resolution | 3840 × 2160 | 3840 × 2160 | 3840 × 2160 |
| | Refreshing Frequency | 60Hz | 60Hz | 60Hz |
| | Brightness | 400nits | 400nits | 400nits |
| | Contrast Ratio | 5000:1 | 4000:1 | 4000:1 |
| | Viewing Angle | 178° | 178° | 178° |
| | Glass Plate | AG (anti-glare) tempered glass, Reflectivity < 1%, 3mm thickness, Mhos 7; Optical bonding, non air gap | | |
| | Life(MTBF) | ≥120,000H | | |
| | Internal Speakers | 20W*2 | | |
| Touch | Touch Points | 32-point touch, 20-point writing | | |
| | Touch Accuracy | Minimum touch object: 1mm; Response time/speed: single touch <5ms, dual touch <7ms | | |
| Input/ Output | Front Input | HDMI 2.0 in*1/ Public USB 3.0*4 (Type A*3, Type C*1)/ Touch USB 2.0*1 (Type A) | | |
| | Rear Input | DP 1.2 in*1/ HDMI 2.0 in*2/ VGA in*1/ VGA Audio in*1 (3.5mm)/ YPbPr in*1/ AV in*1/ RJ45 in*1 | | |
| | Rear Output | Touch USB 2.0*3 (Type B)/ Public USB 3.0*1 (Type A)/ USB (Android) 2.0*1 (Type A) | | |
| Built-in Android | Specification | System Version: Android 8.0, CPU: Cortex A73*2+A53*2 1.5GHz, GPU: MaliG51*4, RAM: DDR4 4G, ROM: 32G | | |
| | Network | Ethernet: 10/100/1000Mbps, WiFi: IEEE 802.11a/b/g/n/ac(2.4GHz+5GHz), Bluetooth: 5.0 | | |
| | | | | |
| Built-In Computer System(OPS) | CPU | Intel Core i5/Customization | | |
| | RAM | 4G DDR4/Customization | | |
| | Storage | 128G SSD/500G HDD/Customization | | |
| | Ethernet | 10/100/1000Mbps | | |
| | Wireless Module | WiFi: IEEE 802.11b/g/n/ac(2.4GHz+5GHz); Bluetooth: 4.2 | | |
| Webcam (Optional) | Operating System | Windows 10 64Bit Professional(Trial) | | |
| | Resolution | 2 million (1080P, 30fps) | | |
| | Sensor | 1 / 2.7 inches, CMOS, 2.07 million effective pixels | | |
| | Scan Mode | Progressive | | |
| | Lens | Focal length: f = 3.2mm; Angle of view: 83°(horizontal), 51°(vertical) | | |
| | Minimum Illumination | 0.5 Lux @ (F2.0, AGC ON) | | |
| Dimensions And Weight | Electronic Shutter | 1/30s ~ 1/10000s | | |
| | DNR (Digital Noise Reduction) | 2D/3D | | |
| | Physical Dimensions(L*W*T)/mm | 1488*928*100 (Without Bracket) 1488*928*123 (With Bracket) | 1733*1070*94.7 (Without Bracket) 1733*1070*126.7 (With Bracket) | 1968*1201*111.8 (Without Bracket) 1968*1201*149.3 (With Bracket) |
| | Frame Width(mm) | Left/Right/Top Frame:15.67 Bottom Frame:71.89 | Left/Right/Top Frame:22.14 Bottom Frame:78.11 | Left/Right/Top Frame:15.67 Bottom Frame:71.89 |
| | Packaging Dimensions(L*W*H)/mm | 1787*270*1150 | 1987*270*1255 | 2214*270*1354 |
| | Net Weight/kg | 45 | 57 | 78 |
| | Gross Weight/kg | 57 | 71 | 102 |
| Standard Packaging Accessories | / | Pen*2 / Remote Control*1 / Power Cable*1(3 Meters) / HDMI Cable*1(5 Meters) / USB Cable*1(A-A, 7.5 Meters) / Manual*2(1 For Wall-mount Bracket, 1 For All-in-one Touch Screen) / Warranty Card*1 / Qualified Certificate*1 / Packing List*1 | | |
| Warranty | / | Touch Screen:3 Years. OPS & Accessories:1 Year. Software Upgrade Free For Lifetime. | | |



Donview Optical Bonding AIO Touch Panel

In its hotly-anticipated L05 series all-in-one interactive touch panel, Donview incorporates the most advanced optical bonding technology to deliver best-in-class interactive displays with improved viewing experience, high touch accuracy, and maximum protection from impact, dust and moisture.

Donview

Shenzhen Donview Electronic Technology Co., Ltd



www.donview.com.cn



facebook.com/DonviewChina



twitter.com/DonviewChina



linkedin.com/company/donviewchina

What Sets Donview Optical Bonding Touch Panel Apart



Unparalleled Viewing Experience

By eliminating the internal reflection between the surface glass and the LCD cell, Donview L05 series optical bonding display provides higher contrast and a wider viewing angle, which allows it to be seen even from the front corner of the room.

Improved Accuracy + Multi-Point Touch/ Writing

Optical bonding reduces parallax by removing the air gap to give you more accurate touch, and brings you perfectly natural and smooth writing experience combined with Donview infrared ultra-thin pen. Up to 32-point touch and 20-point writing brings your team collaboration to a higher level.



More Fashionable Design & Less Weight

Revolution in Ultra-narrow frame design gives you an even nicer product image and thanks to the hardened adhesive applied in the optical bonding, the surface glass of Donview L05 series touch panel is thinner than ever before, which means less weight for transportation and less effort to handle.



Optional Camera

The unique design of USB port at the top of rear back of the panel enables for easy connection with the camera in a user-friendly and tidy way. Better solution, great visual experience!

Higher Configuration

4G RAM + 32G ROM powered by **Android 8.0** enables fast responding and free download from Play Store.



Powerful Interactive Software

L05 series is empowered by Donview's interactive software suite including DonviewBoard, DonviewShare, TouchScreenCast server and more. Marvelous software, excellent presentation! 18+ language options, convenient annotation tools, available with Windows and Android versions



Software Screen Mirroring Function

Enhanced Durability

The advanced optical bonding technology makes the display glass and LCD cell more impact-resistant, which undoubtedly is a significant benefit for safety concern.

Maximum Protection from Dust & Moisture

The elimination of the air gap between the surface glass and the LCD cell prevents dust and moisture from penetrating the glass. This efficiently prolongs the service life of the panel.